

MODEL 4



General Specifications

Tremolo:	Kahler™ Standard
Body Composition:	Basswood
Neck/Fingerboard Composition:	Rock Maple/Quarter-Sawn Rosewood
Machine Heads:	Jackson SG38-07B
Fingerboard Nut Composition:	Phenolic
Fret Wire:	Rockwell C6/Brinell 171
Hardness—Size—	.118 x .114 x .51 x .37
Composition—	18% Nickel Silver
Finish Options:	Black, Pearl White, Red, Cobalt Blue, Black Cherry
Control Functions:	One Volume, One Tone, Jackson Pre-Amp with Mid-Boost, Three 2-Way Mini-toggles

Pickup Specifications

Model Number:	J200 [Two]	ISOBC [One]
Description:	Dual Coil, Bi-level Hum-bucking. Designed for use with active circuitry.	Accentuated High frequency position hum-bucking. Designed for use with active circuitry.
Sr [In K Hz]:	9.90	6.58
Z [@ Sr in MOhms]:	1.8	5.9
Inductance [In Henries]:	2.4	5.3
Q [@ Sr]:	12.6	26.4
Output Level [@ Sr]:	+44.1dB	+56.4dB
Magnetic Structure:	Alnico V	Ceramic
Resistance [In KOhms]:	11.65	8.58